


LOT PX 447
Rev 1

CONTROL

 (Exp.) 2024-07-05
(YYYY - MM - DD)

| PARAMETRES PARAMETERS | | UNITES UNITS | Lysebio | | | | | | | | | |
|--------------------------|--------------------------------------------------------|-----------------|-------------------|-------------------|-------------------------|-------------------|-------------------|-------------------------|-------------------|-------------------|-------------------------|-------------------------|
| | | | CONTROL | | L | CONTROL | | N | CONTROL | | H | TOLERANCES TOLERANCE |
| | | | YUMIZEN | | TOLERANCES TOLERANCE | YUMIZEN | | TOLERANCES TOLERANCE | YUMIZEN | | TOLERANCES TOLERANCE | |
| | | | H1500 HELO 1.x | H2500 HELO 1.x | | H1500 HELO 1.x | H2500 HELO 1.x | | H1500 HELO 1.x | H2500 HELO 1.x | | |
| GB WBC | 10 ⁹ /mm ³ ; 10 ⁹ /l | 2.55 | 2.55 | ± 0.40 | | 7.50 | 7.50 | | ± 1.00 | 17.70 | | |
| GR RBC | 10 ⁶ /mm ³ ; 10 ¹² /l | 2.40 | 2.40 | ± 0.16 | 4.61 | 4.61 | ± 0.20 | 5.19 | 5.19 | ± 0.25 | | |
| HB HGB | g/dl | 6.2 | 6.2 | ± 0.4 | 13.5 | 13.5 | ± 0.5 | 16.5 | 16.5 | ± 0.6 | | |
| | g/l | 62 | 62 | ± 4 | 135 | 135 | ± 5 | 165 | 165 | ± 6 | | |
| | mmol/l | 3.85 | 3.85 | ± 0.25 | 8.38 | 8.38 | ± 0.31 | 10.25 | 10.25 | ± 0.37 | | |
| HT HCT | % | 18.5 | 18.5 | ± 1.5 | 39.4 | 39.4 | ± 2.0 | 48.8 | 48.8 | ± 2.5 | | |
| | l/l | 0.185 | 0.185 | ± 0.015 | 0.394 | 0.394 | ± 0.020 | 0.488 | 0.488 | ± 0.025 | | |
| VGM MCV | µm ³ ; fl | 77.0 | 77.0 | ± 5.0 | 85.5 | 85.5 | ± 5.0 | 94.0 | 94.0 | ± 5.0 | | |
| TGMH MCH | pg | 25.8 | 25.8 | ± 2.0 | 29.3 | 29.3 | ± 2.0 | 31.8 | 31.8 | ± 2.5 | | |
| | fmol | 1.60 | 1.60 | ± 0.12 | 1.82 | 1.82 | ± 0.12 | 1.97 | 1.97 | ± 0.16 | | |
| CCMH MCHC | g/dl | 33.5 | 33.5 | ± 3.0 | 34.3 | 34.3 | ± 3.0 | 33.8 | 33.8 | ± 3.0 | | |
| | g/l | 335 | 335 | ± 30 | 343 | 343 | ± 30 | 338 | 338 | ± 30 | | |
| | mmol/l | 20.83 | 20.83 | ± 1.86 | 21.27 | 21.27 | ± 1.86 | 21.00 | 21.00 | ± 1.86 | | |
| IDR-SD RDW-SD | fl | 40.5 | 40.5 | ± 8.0 | 39.0 | 39.0 | ± 8.0 | 40.0 | 40.0 | ± 8.0 | | |
| IDR-CV RDW-CV | % | 14.0 | 14.0 | ± 4.0 | 12.5 | 12.5 | ± 4.0 | 11.0 | 11.0 | ± 4.0 | | |
| PLA PLT | 10 ⁹ /mm ³ ; 10 ⁹ /l | 64 | 64 | ± 20 | 254 | 254 | ± 30 | 477 | 477 | ± 50 | | |
| PLT-Ox | 10 ⁹ /mm ³ ; 10 ⁹ /l | N/A | 65 | ± 30 | N/A | 250 | ± 40 | N/A | 484 | ± 50 | | |
| VMP MPV | µm ³ ; fl | 8.8 | 8.8 | ± 2.0 | 8.6 | 8.6 | ± 2.0 | 9.4 | 9.4 | ± 2.0 | | |
| NEU | 10 ⁹ /mm ³ ; 10 ⁹ /l | 1.30 | 1.30 | ± 0.35 | 4.10 | 4.10 | ± 0.90 | 12.78 | 12.78 | ± 1.90 | | |
| | % | 51.1 | 51.1 | ± 10.0 | 54.7 | 54.7 | ± 10.0 | 72.2 | 72.2 | ± 10.0 | | |
| LYM | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.76 | 0.76 | ± 0.33 | 2.39 | 2.39 | ± 0.70 | 2.64 | 2.64 | ± 1.50 | | |
| | % | 29.9 | 29.9 | ± 12.0 | 31.9 | 31.9 | ± 8.0 | 14.9 | 14.9 | ± 8.0 | | |
| MON | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.20 | 0.20 | ± 0.20 | 0.44 | 0.44 | ± 0.40 | 0.76 | 0.76 | ± 0.68 | | |
| | % | 7.7 | 7.7 | ± 7.70 | 5.8 | 5.8 | ± 5.2 | 4.3 | 4.3 | ± 3.9 | | |
| EOS | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.19 | 0.19 | ± 0.19 | 0.29 | 0.29 | ± 0.29 | 0.76 | 0.76 | ± 0.76 | | |
| | % | 7.4 | 7.4 | ± 7.40 | 3.8 | 3.8 | ± 3.8 | 4.3 | 4.3 | ± 4.3 | | |
| BAS | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.10 | 0.10 | ± 0.10 | 0.29 | 0.29 | ± 0.19 | 0.76 | 0.76 | ± 0.38 | | |
| | % | 3.9 | 3.9 | ± 2.5 | 3.8 | 3.8 | ± 3.0 | 4.3 | 4.3 | ± 2.5 | | |
| ERB NRBC | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.45 | 0.45 | ± 0.30 | 1.44 | 1.44 | ± 0.45 | 1.22 | 1.22 | ± 0.35 | | |
| | % | 17.8 | 17.8 | ± 8.0 | 19.2 | 19.2 | ± 8.0 | 6.9 | 6.9 | ± 2.0 | | |

BACK / VERSO
Ref: TEMP-0821 Rev.50