

# ABX Minotrol Retic



**LOT** RX 429  
Rev 1

**CONTROL**

(Exp.) 2021-07-05  
(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	ABX											
		CONTROL 1			TOLERANCES TOLERANCE	CONTROL 2			TOLERANCES TOLERANCE	CONTROL 3			TOLERANCES TOLERANCE
		YUMIZEN				YUMIZEN				YUMIZEN			
		H2500				H2500				H2500			
Méthode Manuelle / Manual RETIC	%	<b>1.4</b>			± 1.0	<b>5.5</b>			± 2.2	<b>10.9</b>			± 3.3
RETIC	%	<b>1.75</b>			± 0.88	<b>5.48</b>			± 1.37	<b>11.35</b>			± 2.27
RETIC	10 <sup>6</sup> /mm <sup>3</sup>	<b>0.061</b>			± 0.031	<b>0.188</b>			± 0.047	<b>0.394</b>			± 0.079
	10 <sup>9</sup> /l	<b>61</b>			± 31	<b>188</b>			± 47	<b>394</b>			± 79
MFI MRI *	%	<b>33.1</b>			± 8.0	<b>41.9</b>			± 10.0	<b>49.8</b>			± 12.0
	-	<b>0.331</b>			± 0.080	<b>0.419</b>			± 0.100	<b>0.498</b>			± 0.120
GR RBC	10 <sup>6</sup> /mm <sup>3</sup> ; 10 <sup>12</sup> /l	<b>3.51</b>			± 0.30	<b>3.43</b>			± 0.30	<b>3.47</b>			± 0.30
PIC RANGE	-	<b>13</b>			± 4	<b>13</b>			± 4	<b>13</b>			± 4

1300080026  
Ref: TEMP-0382 Rev.38

\* For research use only in Canada and USA