

# ABX Minotrol Retic



**LOT** RX 425  
Rev 1

**CONTROL**

(Exp.) 2020-11-05  
(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	ABX											
		CONTROL 1			TOLERANCES TOLERANCE	CONTROL 2			TOLERANCES TOLERANCE	CONTROL 3			TOLERANCES TOLERANCE
		YUMIZEN				YUMIZEN				YUMIZEN			
		H2500				H2500				H2500			
Méthode Manuelle / Manual RETIC	%	<b>1.3</b>			± 1.0	<b>5.1</b>			± 2.1	<b>10.9</b>			± 3.3
RETIC	%	<b>1.55</b>			± 0.78	<b>5.05</b>			± 1.26	<b>10.90</b>			± 2.20
RETIC	10 <sup>6</sup> /mm <sup>3</sup>	<b>0.055</b>			± 0.028	<b>0.174</b>			± 0.044	<b>0.382</b>			± 0.076
	10 <sup>9</sup> /l	<b>55</b>			± 28	<b>174</b>			± 44	<b>382</b>			± 76
MFI MRI *	%	<b>22.1</b>			± 8.0	<b>37.0</b>			± 10.0	<b>42.0</b>			± 12.0
	-	<b>0.221</b>			± 0.080	<b>0.370</b>			± 0.100	<b>0.420</b>			± 0.120
GR RBC	10 <sup>6</sup> /mm <sup>3</sup> ; 10 <sup>12</sup> /l	<b>3.56</b>			± 0.30	<b>3.44</b>			± 0.30	<b>3.50</b>			± 0.30
PIC RANGE	-	<b>13</b>			± 4	<b>13</b>			± 4	<b>13</b>			± 4

1300080026  
Ref: TEMP-0382 Rev.38

\* For research use only in Canada and USA