

# ABX Minotrol Retic



**LOT** RX 413  
Rev 1

**CONTROL**

(Exp.) 2018-11-05  
(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	ABX											
		CONTROL			TOLERANCES TOLERANCE	CONTROL			TOLERANCES TOLERANCE	CONTROL			TOLERANCES TOLERANCE
		YUMIZEN		1		YUMIZEN		2		YUMIZEN		3	
		H2500				H2500				H2500			
Méthode Manuelle / Manual RETIC	%	<b>1.3</b>			± 0.7	<b>4.8</b>			± 2.0	<b>9.8</b>			± 3.0
RETIC	%	<b>1.66</b>			± 0.83	<b>5.09</b>			± 1.27	<b>11.20</b>			± 2.24
RETIC	10 <sup>6</sup> /mm <sup>3</sup>	<b>0.056</b>			± 0.028	<b>0.174</b>			± 0.044	<b>0.372</b>			± 0.074
	10 <sup>9</sup> /l	<b>56</b>			± 28	<b>174</b>			± 44	<b>372</b>			± 74
MFI MRI *		<b>31.1</b>			± 8.0	<b>46.6</b>			± 10.0	<b>47.7</b>			± 12.0
GR RBC	10 <sup>6</sup> /mm <sup>3</sup> ; 10 <sup>12</sup> /l	<b>3.40</b>			± 0.30	<b>3.42</b>			± 0.30	<b>3.32</b>			± 0.30
PIC RANGE		<b>13</b>			± 4	<b>13</b>			± 4	<b>13</b>			± 4

Ref: TEMP-0382 Rev.36 1300032515-A

\* For research use only in Canada and USA