

# ABX Minotrol Retic



**LOT** RX 432  
Rev 1

**CONTROL**

(Exp.) 2022-01-05  
(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	ABX											
		CONTROL 1			TOLERANCES TOLERANCE	CONTROL 2			TOLERANCES TOLERANCE	CONTROL 3			TOLERANCES TOLERANCE
		YUMIZEN				YUMIZEN				YUMIZEN			
Méthode Manuelle / Manual RETIC	%	<b>1.4</b>			± 0.7	<b>5.5</b>			± 2.2	<b>12.2</b>			± 3.7
RETIC	%	<b>1.67</b>			± 0.84	<b>5.02</b>			± 1.26	<b>10.54</b>			± 2.11
RETIC	10 <sup>6</sup> /mm <sup>3</sup>	<b>0.058</b>			± 0.029	<b>0.175</b>			± 0.044	<b>0.367</b>			± 0.073
	10 <sup>9</sup> /l	<b>58</b>			± 29	<b>175</b>			± 44	<b>367</b>			± 73
MFI MRI *	%	<b>28.5</b>			± 8.0	<b>38.3</b>			± 10.0	<b>41.5</b>			± 12.0
	-	<b>0.285</b>			± 0.080	<b>0.383</b>			± 0.100	<b>0.415</b>			± 0.120
GR RBC	10 <sup>6</sup> /mm <sup>3</sup> ; 10 <sup>12</sup> /l	<b>3.49</b>			± 0.30	<b>3.48</b>			± 0.30	<b>3.48</b>			± 0.30
PIC RANGE	-	<b>13</b>			± 8	<b>13</b>			± 8	<b>13</b>			± 8

1300080026  
Ref: TEMP-0382 Rev.40

\* For research use only in Canada and USA