

# ABX Minotrol Retic



**LOT** RX 412  
Rev 1

**CONTROL**

(Exp.) 2018-09-05  
(YYYY - MM - DD)

| PARAMETRES<br>PARAMETERS              | UNITES<br>UNITS   | ABX          |  |   |                         |              |  |   |                         |              |  |   |                         |
|---------------------------------------|---|--------------|--|---|-------------------------|--------------|--|---|-------------------------|--------------|--|---|-------------------------|
|                                       |   | CONTROL      |  |   | TOLERANCES<br>TOLERANCE | CONTROL      |  |   | TOLERANCES<br>TOLERANCE | CONTROL      |  |   | TOLERANCES<br>TOLERANCE |
|                                       |   | YUMIZEN      |  | 1 |                         | YUMIZEN      |  | 2 |                         | YUMIZEN      |  | 3 |                         |
|                                       |   | H2500        |  |   |                         | H2500        |  |   |                         | H2500        |  |   |                         |
| Méthode<br>Manuelle / Manual<br>RETIC | %   | <b>1.7</b>   |  |   | ± 0.9                   | <b>5.5</b>   |  |   | ± 2.2                   | <b>10.2</b>  |  |   | ± 3.1                   |
| RETIC                                 | %   | <b>1.93</b>  |  |   | ± 0.97                  | <b>5.26</b>  |  |   | ± 1.32                  | <b>10.90</b> |  |   | ± 2.18                  |
| RETIC                                 | 10 <sup>6</sup> /mm <sup>3</sup>                          | <b>0.067</b> |  |   | ± 0.034                 | <b>0.183</b> |  |   | ± 0.046                 | <b>0.378</b> |  |   | ± 0.076                 |
|                                       | 10 <sup>9</sup> /l  | <b>67</b>    |  |   | ± 34                    | <b>183</b>   |  |   | ± 46                    | <b>378</b>   |  |   | ± 76                    |
| MFI MRI *                             |   | <b>34.8</b>  |  |   | ± 8.0                   | <b>42.2</b>  |  |   | ± 10.0                  | <b>45.4</b>  |  |   | ± 12.0                  |
| GR RBC                                | 10 <sup>6</sup> /mm <sup>3</sup> ;<br>10 <sup>12</sup> /l | <b>3.45</b>  |  |   | ± 0.30                  | <b>3.48</b>  |  |   | ± 0.30                  | <b>3.47</b>  |  |   | ± 0.30                  |
| PIC RANGE                             |   | <b>13</b>    |  |   | ± 4                     | <b>13</b>    |  |   | ± 4                     | <b>13</b>    |  |   | ± 4                     |

1300032515-A  
Ref: TEMP-0382 Rev.36

\* For research use only in Canada and USA