


LOT PX 430
Rev 2

CONTROL

 (Exp.) 2021-09-05
(YYYY - MM - DD)

PARAMETRES PARAMETERS		UNITES UNITS	Lysebio									
			CONTROL		L	CONTROL		N	CONTROL		H	TOLERANCES TOLERANCE
			YUMIZEN		TOLERANCES TOLERANCE	YUMIZEN		TOLERANCES TOLERANCE	YUMIZEN		TOLERANCES TOLERANCE	
			H1500	H2500		H1500	H2500		H1500	H2500		
GB	WBC	10 ⁹ /mm ³ ; 10 ⁹ /l	2.40	2.40	± 0.40	6.85	6.85	± 1.00	17.13	17.13	± 2.20	
GR	RBC	10 ⁶ /mm ³ ; 10 ¹² /l	2.24	2.24	± 0.16	4.65	4.65	± 0.20	5.24	5.24	± 0.25	
HB	HGB	g/dl	5.6	5.6	± 0.4	13.5	13.5	± 0.5	16.5	16.5	± 0.6	
		g/l	56	56	± 4	135	135	± 5	165	165	± 6	
		mmol/l	3.48	3.48	± 0.25	8.38	8.38	± 0.31	10.25	10.25	± 0.37	
HT	HCT	%	16.4	16.4	± 1.5	37.4	37.4	± 2.0	46.1	46.1	± 2.5	
		l/l	0.164	0.164	± 0.015	0.374	0.374	± 0.020	0.461	0.461	± 0.025	
VGM	MCV	µm ³ ; fl	73.0	73.0	± 5.0	80.5	80.5	± 5.0	88.0	88.0	± 5.0	
TGMH	MCH	pg	25.0	25.0	± 2.0	29.0	29.0	± 2.0	31.5	31.5	± 2.5	
		fmol	1.55	1.55	± 0.12	1.80	1.80	± 0.12	1.96	1.96	± 0.16	
CCMH	MCHC	g/dl	34.2	34.2	± 3.0	36.1	36.1	± 3.0	35.8	35.8	± 3.0	
		g/l	342	342	± 30	361	361	± 30	358	358	± 30	
		mmol/l	21.27	21.27	± 1.86	22.40	22.40	± 1.86	22.22	22.22	± 1.86	
IDR-CV	RDW-CV	%	14.0	14.0	± 4.0	12.0	12.0	± 4.0	12.0	12.0	± 4.0	
PLAQ.	PLTS	10 ³ /mm ³ ; 10 ⁹ /l	63	63	± 20	249	249	± 30	492	492	± 50	
VPM	MPV	µm ³ ; fl	9.2	9.2	± 2.0	10.1	10.1	± 2.0	9.3	9.3	± 2.0	
NEUT		#	1.29	1.29	± 0.35	3.72	3.72	± 0.90	11.39	11.39	± 1.90	
		%	53.7	53.7	± 10.0	54.3	54.3	± 10.0	66.5	66.5	± 10.0	
LYMPHO		#	0.67	0.67	± 0.33	1.71	1.71	± 0.70	2.23	2.23	± 1.50	
		%	28.1	28.1	± 12.0	24.9	24.9	± 8.0	13.0	13.0	± 8.0	
MONO		#	0.14	0.14	± 0.14	0.63	0.63	± 0.57	1.76	1.76	± 1.58	
		%	5.7	5.7	± 5.7	9.2	9.2	± 8.3	10.3	10.3	± 9.3	
EOS		#	0.19	0.19	± 0.19	0.45	0.45	± 0.45	0.89	0.89	± 0.89	
		%	8.0	8.0	± 8.0	6.6	6.6	± 6.6	5.2	5.2	± 5.2	
BASO		#	0.11	0.11	± 0.11	0.34	0.34	± 0.34	0.86	0.86	± 0.86	
		%	4.6	4.6	± 4.6	5.0	5.0	± 5.0	5.0	5.0	± 5.0	
IDR-SD	RDW-SD	fl	38.0	38.0	± 6.0	37.5	37.5	± 6.0	41.0	41.0	± 6.0	
ERB	NRBC	#	0.39	0.39	± 0.20	1.07	1.07	± 0.30	1.11	1.11	± 0.25	
		%	16.4	16.4	± 6.0	15.6	15.6	± 5.0	6.5	6.5	± 1.5	
PLTS	OPT	10 ³ /mm ³ ; 10 ⁹ /l	N/A	71	± 30	N/A	251	± 40	N/A	512	± 50	

1300074625
BACK / VERSO
Ref. TEMP-0821 Rev.45