

# ABX Minocal



**LOT**

**CX 477**

**CAL**



**(Exp.) 2023-01-05**

(YYYY - MM - DD)

Rev 1

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF								TOLERANCES TOLERANCE
		YUMIZEN V1.0 to V2.x				YUMIZEN since V3				
		H550	H500 OT H500 CT			H500 OT	H500 CT H550			
GB WBC	10 <sup>3</sup> /mm <sup>3</sup> ;10 <sup>9</sup> /l	<b>8.78</b>	<b>8.78</b>			<b>8.45</b>	<b>9.16</b>			± 0.20
GR RBC	10 <sup>6</sup> /mm <sup>3</sup> ;10 <sup>12</sup> /l	<b>4.62</b>	<b>4.62</b>			<b>4.54</b>	<b>4.66</b>			± 0.06
HB HGB	g/dl	<b>13.6</b>	<b>13.6</b>			<b>13.4</b>	<b>13.7</b>			± 0.2
	g/l	<b>136</b>	<b>136</b>			<b>134</b>	<b>137</b>			± 2
	mmol/l	<b>8.45</b>	<b>8.45</b>			<b>8.32</b>	<b>8.51</b>			± 0.12
HT HCT	%	<b>39.3</b>	<b>39.3</b>			<b>37.3</b>	<b>38.3</b>			± 1.0
	l/l	<b>0.393</b>	<b>0.393</b>			<b>0.373</b>	<b>0.383</b>			± 0.010
PLA PLT	10 <sup>3</sup> /mm <sup>3</sup> ;10 <sup>9</sup> /l	<b>270</b>	<b>270</b>			<b>255</b>	<b>275</b>			± 10
VMP MPV	μm <sup>3</sup> ; fl	<b>11.1</b>	<b>11.1</b>			<b>10.6</b>	<b>11.0</b>			± 0.5

Ref: TEMP-0387 Rev.48 BACK / VERSO 1300105208