

ABX Minocal



LOT

CX 480

CAL



(Exp.) 2023-04-05

Rev 1

(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF								TOLERANCES TOLERANCE
		YUMIZEN V1.0 to V2.x				YUMIZEN since V3				
		H550	H500 OT H500 CT			H500 OT	H500 CT H550			
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.70	8.70			8.60	8.60			± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.57	4.57			4.53	4.53			± 0.06
HB HGB	g/dl	13.2	13.2			13.0	13.0			± 0.2
	g/l	132	132			130	130			± 2
	mmol/l	8.20	8.20			8.07	8.07			± 0.12
HT HCT	%	38.2	38.2			37.5	36.2			± 1.0
	l/l	0.382	0.382			0.375	0.362			± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	250	250			244	274			± 10
VMP MPV	μm ³ ; fl	10.8	10.8			9.2	9.2			± 0.5

Ref: TEMP-0387 Rev.48 BACK / VERSO 1300105208