

ABX Minocal



LOT

CX 481

CAL



(Exp.) 2023-05-05

(YYYY - MM - DD)

Rev 2

| PARAMETRES PARAMETERS | UNITES UNITS | WHITEDIFF | | | | | | | | TOLERANCES TOLERANCE |
|--------------------------|---|----------------------|--------------------|--|--|------------------|-----------------|--|--|-------------------------|
| | | YUMIZEN V1.0 to V2.x | | | | YUMIZEN since V3 | | | | |
| | | H550 | H500 OT H500 CT | | | H500 OT | H500 CT H550 | | | |
| GB WBC | 10 ³ /mm ³ ;10 ⁹ /l | 8.80 | 8.80 | | | 8.80 | 8.80 | | | ± 0.20 |
| GR RBC | 10 ⁶ /mm ³ ;10 ¹² /l | 4.42 | 4.42 | | | 4.45 | 4.45 | | | ± 0.06 |
| HB HGB | g/dl | 12.5 | 12.5 | | | 12.5 | 12.5 | | | ± 0.2 |
| | g/l | 125 | 125 | | | 125 | 125 | | | ± 2 |
| | mmol/l | 7.76 | 7.76 | | | 7.76 | 7.76 | | | ± 0.12 |
| HT HCT | % | 36.5 | 36.5 | | | 35.2 | 34.4 | | | ± 1.0 |
| | l/l | 0.365 | 0.365 | | | 0.352 | 0.344 | | | ± 0.010 |
| PLA PLT | 10 ³ /mm ³ ;10 ⁹ /l | 248 | 248 | | | 275 | 278 | | | ± 10 |
| VMP MPV | µm ³ ; fl | 10.7 | 10.7 | | | 9.2 | 9.2 | | | ± 0.5 |

Ref: TEMP-0387 Rev.48 BACK / VERSO 1300105208