

ABX Minocal



(Exp.) 2024-02-05
(YYYY - MM - DD)

LOT

CX 490

CAL

Rev 1

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF								TOLERANCES TOLERANCE
		YUMIZEN V1.0 to V2.x				YUMIZEN since V3				
		H550	H500 OT H500 CT			H500 OT	H500 CT H550			
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.85	8.85			8.85	8.85			± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.47	4.47			4.47	4.47			± 0.06
HB HGB	g/dl	12.6	12.6			12.8	12.8			± 0.2
	g/l	126	126			128	128			± 2
	mmol/l	7.82	7.82			7.95	7.95			± 0.12
HT HCT	%	36.9	36.9			34.8	35.0			± 1.0
	l/l	0.369	0.369			0.348	0.350			± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	252	252			263	272			± 10
VMP MPV	μm ³ ; fl	10.2	10.2			N/A	N/A			± 0.5

Ref: TEMP-0387 Rev.51 BACK / VERSO 1300113555