

**LOT** BFI 2445  
Rev 1

**CONTROL**

 (Exp.) 2024-03-05  
(YYYY - MM - DD)

| PARAMETRES<br>PARAMETERS | UNITES<br>UNITS    | BFTROL           |                  |          |          |                  |                         |                  |          |                         |          |  |
|--------------------------|--------------------|------------------|------------------|----------|----------|------------------|-------------------------|------------------|----------|-------------------------|----------|--|
|                          |                    | CONTROL          |                  |          |          |                  | TOLERANCES<br>TOLERANCE | CONTROL          |          |                         |          |  |
|                          |                    | RANGE            |                  | RANGE    |          | RANGE            |                         | RANGE            |          | TOLERANCES<br>TOLERANCE |          |  |
|                          |                    | YUMIZEN<br>H1500 | YUMIZEN<br>H2500 | HELO 2.0 | HELO 2.0 | YUMIZEN<br>H1500 |                         | YUMIZEN<br>H2500 | HELO 2.0 |                         | HELO 2.0 |  |
| BFWBC                    | 10 <sup>6</sup> /l | <b>227</b>       | <b>227</b>       |          |          | ± 91             | <b>871</b>              | <b>871</b>       |          |                         | ± 218    |  |
| BFRBC                    | 10 <sup>6</sup> /l | <b>76883</b>     | <b>76883</b>     |          |          | ± 19221          | <b>498482</b>           | <b>498482</b>    |          |                         | ± 124621 |  |
| BFMN                     | 10 <sup>6</sup> /l | <b>59</b>        | <b>59</b>        |          |          | ± 21             | <b>87</b>               | <b>87</b>        |          |                         | ± 35     |  |
|                          | %                  | <b>26</b>        | <b>26</b>        |          |          | ± 9              | <b>10</b>               | <b>10</b>        |          |                         | ± 4      |  |
| BFPN                     | 10 <sup>6</sup> /l | <b>168</b>       | <b>168</b>       |          |          | ± 59             | <b>784</b>              | <b>784</b>       |          |                         | ± 196    |  |
|                          | %                  | <b>74</b>        | <b>74</b>        |          |          | ± 26             | <b>90</b>               | <b>90</b>        |          |                         | ± 23     |  |

Ref: TEMP-5502 Rev.07