

ABX Minocal



LOT

CX 494

CAL



(Exp.) 2024-06-05

Rev 1

(YYYY - MM - DD)

| PARAMETRES PARAMETERS | UNITES UNITS | WHITEDIFF | | | | | | | | TOLERANCES TOLERANCE |
|--------------------------|---|----------------------|--------------------|--|--|------------------|-----------------|--|--|-------------------------|
| | | YUMIZEN V1.0 to V2.x | | | | YUMIZEN since V3 | | | | |
| | | H550 | H500 OT H500 CT | | | H500 OT | H500 CT H550 | | | |
| GB WBC | 10 ³ /mm ³ ;10 ⁹ /l | 8.85 | 8.85 | | | 8.88 | 8.88 | | | ± 0.20 |
| GR RBC | 10 ⁶ /mm ³ ;10 ¹² /l | 4.51 | 4.51 | | | 4.45 | 4.45 | | | ± 0.06 |
| HB HGB | g/dl | 13.0 | 13.0 | | | 13.0 | 13.0 | | | ± 0.2 |
| | g/l | 130 | 130 | | | 130 | 130 | | | ± 2 |
| | mmol/l | 8.07 | 8.07 | | | 8.07 | 8.07 | | | ± 0.12 |
| HT HCT | % | 37.9 | 37.9 | | | 36.8 | 36.6 | | | ± 1.0 |
| | l/l | 0.379 | 0.379 | | | 0.368 | 0.366 | | | ± 0.010 |
| PLA PLT | 10 ³ /mm ³ ;10 ⁹ /l | 242 | 242 | | | 250 | 267 | | | ± 10 |
| VMP MPV | μm ³ ; fl | 10.3 | 10.3 | | | N/A | N/A | | | ± 0.5 |

Ref: TEMP-0387 Rev.51 BACK / VERSO 1300113555