


LOT PX 443
Rev 2

CONTROL

 (Exp.) 2023-11-05
(YYYY - MM - DD)

| PARAMETRES PARAMETERS | UNITES UNITS | Whitediff | | | | | | | | | | | | TOLERANCES TOLERANCE | | | |
|--------------------------|--|----------------------|--------------------|--------------------|---------------------|-------------------------|----------------------|--------------------|--------------------|---------------------|-------------------------|----------------------|--------------------|-------------------------|--------------------|-------------------------|---------------------|
| | | CONTROL | | | | TOLERANCES TOLERANCE | CONTROL | | | | TOLERANCES TOLERANCE | CONTROL | | | | TOLERANCES TOLERANCE | |
| | | YUMIZEN | | | | | YUMIZEN | | | | | YUMIZEN | | | | | |
| | | H550 V1.0 to V2.x | H500 OT H500 CT | H500 OT H500 CT | H500 CT Since V3 | | H550 V1.0 to V2.x | H500 OT H500 CT | H500 OT H500 CT | H500 CT Since V3 | | H550 V1.0 to V2.x | H500 OT H500 CT | | H500 OT H500 CT | | H500 CT Since V3 |
| GB WBC | 10 ⁹ /mm ³ ; 10 ⁹ /l | 3.00 | 3.00 | 3.00 | 3.00 | ± 0.40 | 8.40 | 8.40 | 8.40 | 8.40 | ± 1.00 | 18.30 | 18.30 | 18.30 | 18.30 | ± 2.20 | |
| GR RBC | 10 ⁶ /mm ³ ; 10 ¹² /l | 2.24 | 2.24 | 2.24 | 2.24 | ± 0.16 | 4.66 | 4.66 | 4.66 | 4.66 | ± 0.20 | 5.28 | 5.28 | 5.28 | 5.28 | ± 0.25 | |
| HB HGB | g/dl | 5.7 | 5.7 | 5.7 | 5.7 | ± 0.4 | 13.2 | 13.2 | 13.1 | 13.1 | ± 0.5 | 16.3 | 16.3 | 16.2 | 16.2 | ± 0.6 | |
| | g/l | 57 | 57 | 57 | 57 | ± 4 | 132 | 132 | 131 | 131 | ± 5 | 163 | 163 | 162 | 162 | ± 6 | |
| | mmol/l | 3.54 | 3.54 | 3.54 | 3.54 | ± 0.25 | 8.20 | 8.20 | 8.14 | 8.14 | ± 0.31 | 10.12 | 10.12 | 10.06 | 10.06 | ± 0.37 | |
| HT HCT | % | 17.5 | 17.5 | 16.6 | 16.3 | ± 1.5 | 40.5 | 40.5 | 38.8 | 37.9 | ± 2.0 | 49.6 | 49.6 | 48.2 | 47.2 | ± 2.5 | |
| | l/l | 0.175 | 0.175 | 0.166 | 0.163 | ± 0.015 | 0.405 | 0.405 | 0.388 | 0.379 | ± 0.020 | 0.496 | 0.496 | 0.482 | 0.472 | ± 0.025 | |
| VGM MCV | µm ³ ·fl | 78.0 | 78.0 | 74.2 | 72.8 | ± 5.0 | 87.0 | 87.0 | 83.2 | 81.4 | ± 5.0 | 94.0 | 94.0 | 91.2 | 89.4 | ± 5.0 | |
| TGMH MCH | pg | 25.4 | 25.4 | 25.4 | 25.4 | ± 2.0 | 28.3 | 28.3 | 28.1 | 28.1 | ± 2.0 | 30.9 | 30.9 | 30.7 | 30.7 | ± 2.5 | |
| | fmol | 1.58 | 1.58 | 1.58 | 1.58 | ± 0.12 | 1.76 | 1.76 | 1.75 | 1.75 | ± 0.12 | 1.92 | 1.92 | 1.91 | 1.91 | ± 0.16 | |
| CCMH MCHC | g/dl | 32.6 | 32.6 | 34.3 | 35.0 | ± 3.0 | 32.6 | 32.6 | 33.8 | 34.5 | ± 3.0 | 32.8 | 32.8 | 33.6 | 34.3 | ± 3.0 | |
| | g/l | 326 | 326 | 343 | 350 | ± 30 | 326 | 326 | 338 | 345 | ± 30 | 328 | 328 | 336 | 343 | ± 30 | |
| | mmol/l | 20.24 | 20.24 | 21.30 | 21.74 | ± 1.86 | 20.24 | 20.24 | 20.99 | 21.42 | ± 1.86 | 20.37 | 20.37 | 20.87 | 21.30 | ± 1.86 | |
| IDR-SD RDW-SD | fl | 48.0 | 48.0 | 40.7 | 40.7 | ± 8.0 | 44.5 | 44.5 | 39.7 | 39.7 | ± 8.0 | 46.0 | 46.0 | 38.6 | 38.6 | ± 8.0 | |
| IDR-CV RDW-CV | % | 17.5 | 17.5 | 18.3 | 18.3 | ± 4.0 | 14.0 | 14.0 | 15.9 | 15.9 | ± 4.0 | 13.5 | 13.5 | 13.9 | 13.9 | ± 4.0 | |
| PLA. PLT | 10 ⁹ /mm ³ ; 10 ⁹ /l | 65 | 65 | 85 | 82 | ± 20 | 250 | 250 | 285 | 274 | ± 30 | 497 | 497 | 552 | 528 | ± 50 | |
| VMP MPV | µm ³ ·fl | 9.7 | 9.7 | 10.7 | 10.7 | ± 2.0 | 9.5 | 9.5 | 9.6 | 9.6 | ± 2.0 | 10.8 | 10.8 | 10.3 | 10.3 | ± 2.0 | |
| NEU | 10 ⁹ /mm ³ ; 10 ⁹ /l | 1.28 | 1.28 | 1.27 | 1.27 | ± 0.35 | 3.93 | 3.93 | 3.81 | 3.81 | ± 0.90 | 12.44 | 12.44 | 12.22 | 12.22 | ± 1.90 | |
| | % | 42.8 | 42.8 | 43.7 | 43.7 | ± 10.0 | 46.8 | 46.8 | 45.3 | 45.3 | ± 10.0 | 68.0 | 68.0 | 66.8 | 66.8 | ± 10.0 | |
| LYM | 10 ⁹ /mm ³ ; 10 ⁹ /l | 1.19 | 1.19 | 1.17 | 1.17 | ± 0.33 | 3.44 | 3.44 | 3.54 | 3.54 | ± 0.70 | 3.68 | 3.68 | 3.81 | 3.81 | ± 1.50 | |
| | % | 39.8 | 39.8 | 38.1 | 38.1 | ± 12.0 | 41.0 | 41.0 | 42.2 | 42.2 | ± 8.0 | 20.1 | 20.1 | 20.8 | 20.8 | ± 8.0 | |
| MON | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.25 | 0.25 | 0.24 | 0.24 | ± 0.24 | 0.52 | 0.52 | 0.50 | 0.50 | ± 0.50 | 0.71 | 0.71 | 0.79 | 0.79 | ± 0.71 | |
| | % | 8.4 | 8.4 | 7.9 | 7.9 | ± 7.9 | 6.2 | 6.2 | 6.0 | 6.0 | ± 6.0 | 3.9 | 3.9 | 4.3 | 4.3 | ± 3.9 | |
| EOS | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.17 | 0.17 | 0.21 | 0.21 | ± 0.17 | 0.25 | 0.25 | 0.29 | 0.29 | ± 0.25 | 0.73 | 0.73 | 0.75 | 0.75 | ± 0.73 | |
| | % | 5.5 | 5.5 | 6.8 | 6.8 | ± 5.5 | 3.0 | 3.0 | 3.5 | 3.5 | ± 3.0 | 4.0 | 4.0 | 4.1 | 4.1 | ± 4.0 | |
| BAS | 10 ⁹ /mm ³ ; 10 ⁹ /l | 0.11 | 0.11 | 0.11 | 0.11 | ± 0.11 | 0.25 | 0.25 | 0.25 | 0.25 | ± 0.25 | 0.73 | 0.73 | 0.73 | 0.73 | ± 0.73 | |
| | % | 3.5 | 3.5 | 3.5 | 3.5 | ± 3.5 | 3.0 | 3.0 | 3.0 | 3.0 | ± 3.0 | 4.0 | 4.0 | 4.0 | 4.0 | ± 4.0 | |
| IMG | 10 ⁹ /mm ³ ; 10 ⁹ /l | N/A | N/A | 0.08 | 0.08 | ± 0.08 | N/A | N/A | 0.29 | 0.29 | ± 0.29 | N/A | N/A | 0.92 | 0.92 | ± 0.92 | |
| | % | N/A | N/A | 2.6 | 2.6 | ± 2.6 | N/A | N/A | 3.5 | 3.5 | ± 3.5 | N/A | N/A | 5.0 | 5.0 | ± 5.0 | |

Ref: TEMP-0821 Rev.49 FRONT / RECTO