

ABX Minocal



LOT		CX 473		CAL		(Exp.) 2022-09-05 (YYYY - MM - DD)						
		Rev 1		WHITEDIFF								
PARAMETRES PARAMETERS	UNITES UNITS	YUMIZEN V1.0 to V2.x			YUMIZEN since V3						TOLERANCES TOLERANCE	
		H550	H500 OT H500 CT		H500 OT	H500 CT H550						
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	9.00	9.00		9.04	9.04					± 0.20	
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.51	4.51		4.42	4.42					± 0.06	
HB HGB	g/dl	12.8	12.8		12.8	12.8					± 0.2	
	g/l	128	128		128	128					± 2	
	mmol/l	7.95	7.95		7.97	7.97					± 0.12	
HT HCT	%	37.4	37.4		35.8	35.8					± 1.0	
	l/l	0.374	0.374		0.358	0.358					± 0.010	
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	260	260		269	269					± 10	
VMP MPV	μm ³ ; fl	10.3	10.3		10.4	10.4					± 0.5	

Ref: TEMP-0387 Rev.48 BACK / VERSO 1300105208