

ABX Minocal



LOT		CX 492		CAL		(Exp.) 2024-04-05 (YYYY - MM - DD)							
		Rev 1		WHITEDIFF									
PARAMETRES PARAMETERS	UNITES UNITS	YUMIZEN V1.0 to V2.x			YUMIZEN since V3						TOLERANCES TOLERANCE		
		H550	H500 OT H500 CT		H500 OT	H500 CT H550							
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.90	8.90		8.91	8.91					± 0.20		
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.54	4.54		4.51	4.51					± 0.06		
HB HGB	g/dl	13.0	13.0		13.1	13.1					± 0.2		
	g/l	130	130		131	131					± 2		
	mmol/l	8.07	8.07		8.14	8.14					± 0.12		
HT HCT	%	37.9	37.9		36.1	36.7					± 1.0		
	l/l	0.379	0.379		0.361	0.367					± 0.010		
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	236	236		244	260					± 10		
VMP MPV	µm ³ ; fl	10.9	10.9		N/A	N/A					± 0.5		

1300113555
BACK / VERSO
Ref. TEMP-0387 Rev.51