

ABX Minocal



LOT

CX 485

CAL



(Exp.) 2023-09-05

(YYYY - MM - DD)

Rev 1

| PARAMETRES PARAMETERS | UNITES UNITS | WHITEDIFF | | | | | | | | TOLERANCES TOLERANCE |
|--------------------------|---|----------------------|--------------------|--|--|------------------|-----------------|--|--|-------------------------|
| | | YUMIZEN V1.0 to V2.x | | | | YUMIZEN since V3 | | | | |
| | | H550 | H500 OT H500 CT | | | H500 OT | H500 CT H550 | | | |
| GB WBC | 10 ³ /mm ³ ;10 ⁹ /l | 9.10 | 9.10 | | | 9.10 | 9.10 | | | ± 0.20 |
| GR RBC | 10 ⁶ /mm ³ ;10 ¹² /l | 4.58 | 4.58 | | | 4.53 | 4.53 | | | ± 0.06 |
| HB HGB | g/dl | 13.0 | 13.0 | | | 13.0 | 13.0 | | | ± 0.2 |
| | g/l | 130 | 130 | | | 130 | 130 | | | ± 2 |
| | mmol/l | 8.07 | 8.07 | | | 8.07 | 8.07 | | | ± 0.12 |
| HT HCT | % | 38.0 | 38.0 | | | 36.6 | 36.1 | | | ± 1.0 |
| | l/l | 0.380 | 0.380 | | | 0.366 | 0.361 | | | ± 0.010 |
| PLA PLT | 10 ³ /mm ³ ;10 ⁹ /l | 246 | 246 | | | 275 | 270 | | | ± 10 |
| VMP MPV | μm ³ ; fl | 10.0 | 10.0 | | | N/A | N/A | | | ± 0.5 |

Ref: TEMP-0387 Rev.49 BACK / VERSO 1300113555