

ABX Minocal



LOT		CX 480		CAL		(Exp.) 2023-04-05 (YYYY - MM - DD)					
PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN V1.0 to V2.x		YUMIZEN since V3							
		H550	H500 OT H500 CT		H500 OT	H500 CT H550					
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.70	8.70		8.60	8.60					± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.57	4.57		4.53	4.53					± 0.06
HB HGB	g/dl	13.2	13.2		13.0	13.0					± 0.2
	g/l	132	132		130	130					± 2
	mmol/l	8.20	8.20		8.07	8.07					± 0.12
HT HCT	%	38.2	38.2		37.5	36.2					± 1.0
	l/l	0.382	0.382		0.375	0.362					± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	250	250		244	274					± 10
VMP MPV	μm ³ ; fl	10.8	10.8		9.2	9.2					± 0.5

 1300105208
 BACK / VERSO
 Ref. TEMP-0387 Rev.48