

ABX Minocal



LOT		CX 494		CAL		(Exp.) 2024-06-05 (YYYY - MM - DD)							
		Rev 1		WHITEDIFF									
PARAMETRES PARAMETERS		UNITES UNITS		YUMIZEN V1.0 to V2.x		YUMIZEN since V3						TOLERANCES TOLERANCE	
				H550	H500 OT H500 CT		H500 OT	H500 CT H550					
GB	WBC	10 ³ /mm ³ ;10 ⁹ /l	8.85	8.85		8.88	8.88						± 0.20
GR	RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.51	4.51		4.45	4.45						± 0.06
HB	HGB	g/dl	13.0	13.0		13.0	13.0						± 0.2
		g/l	130	130		130	130						± 2
		mmol/l	8.07	8.07		8.07	8.07						± 0.12
HT	HCT	%	37.9	37.9		36.8	36.6						± 1.0
		l/l	0.379	0.379		0.368	0.366						± 0.010
PLA	PLT	10 ³ /mm ³ ;10 ⁹ /l	242	242		250	267						± 10
VMP	MPV	µm ³ ; fl	10.3	10.3		N/A	N/A						± 0.5

1300113555
BACK / VERSO
Ref. TEMP-0387 Rev.51