

ABX Minocal



LOT

CX 490

CAL



(Exp.) 2024-02-05

(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN V1.0 to V2.x			YUMIZEN since V3						
		H550	H500 OT H500 CT		H500 OT	H500 CT H550					
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.85	8.85		8.85	8.85					± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.47	4.47		4.47	4.47					± 0.06
HB HGB	g/dl	12.6	12.6		12.8	12.8					± 0.2
	g/l	126	126		128	128					± 2
	mmol/l	7.82	7.82		7.95	7.95					± 0.12
HT HCT	%	36.9	36.9		34.8	35.0					± 1.0
	l/l	0.369	0.369		0.348	0.350					± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	252	252		263	272					± 10
VMP MPV	µm ³ ; fl	10.2	10.2		N/A	N/A					± 0.5

1300113555
BACK / VERSO
Ref. TEMP-0387 Rev.51