

ABX Minocal



LOT

CX 478

CAL



(Exp.) 2023-02-05

(YYYY - MM - DD)

Rev 2

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF								TOLERANCES TOLERANCE
		YUMIZEN V1.0 to V2.x				YUMIZEN since V3				
		H550	H500 OT H500 CT			H500 OT	H500 CT H550			
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.80	8.80			8.75	8.75			± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.59	4.59			4.50	4.50			± 0.06
HB HGB	g/dl	13.1	13.1			13.0	13.3			± 0.2
	g/l	131	131			130	133			± 2
	mmol/l	8.14	8.14			8.07	8.26			± 0.12
HT HCT	%	38.3	38.3			35.3	35.7			± 1.0
	l/l	0.383	0.383			0.353	0.357			± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	249	249			264	274			± 10
VMP MPV	µm ³ ; fl	11.0	11.0			9.2	9.2			± 0.5

Ref: TEMP-0387 Rev.48 BACK / VERSO 1300105208