

ABX Minocal



IVD

LOT		CX 496		CAL		(Exp.) 2024-08-05 (YYYY - MM - DD)							
		Rev 1		WHITEDIFF									
PARAMETRES PARAMETERS	UNITES UNITS	YUMIZEN V1.0 to V2.x			YUMIZEN since V3						TOLERANCES TOLERANCE		
		H550	H500 OT H500 CT		H500 OT	H500 CT H550							
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	9.00	9.00		9.00	9.00					± 0.20		
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.48	4.48		4.42	4.42					± 0.06		
HB HGB	g/dl	12.8	12.8		12.8	12.8					± 0.2		
	g/l	128	128		128	128					± 2		
	mmol/l	7.95	7.95		7.95	7.95					± 0.12		
HT HCT	%	37.2	37.2		36.2	35.4					± 1.0		
	l/l	0.372	0.372		0.362	0.354					± 0.010		
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	239	239		240	260					± 10		
VMP MPV	µm ³ ; fl	10.0	10.0		N/A	N/A					± 0.5		

1300113555
BACK / VERSO
Ref. TEMP-0387 Rev.51