

ABX Minocal



LOT

CX 496

CAL



(Exp.) 2024-08-05

(YYYY - MM - DD)

Rev **2**

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN		YUMIZEN	YUMIZEN	YUMIZEN		YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550		H500 OT	H500 CT H550	H560		H500 OT H500E OT	H500 CT H500E CT H550 H550E	H560	
v1.0 to v2.x		v3.x Only			v3.0 to v3.3		Since v4.x			Since v3.4	
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	9.00		9.00	9.00	9.00		8.90	8.90	8.90	± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.48		4.42	4.42	4.42		4.50	4.50	4.50	± 0.06
HB HGB	g/dl	12.8		12.8	12.8	12.8		13.0	13.0	13.0	± 0.2
	g/l	128		128	128	128		130	130	130	± 2
	mmol/l	7.95		7.95	7.95	7.95		8.07	8.07	8.07	± 0.12
HT HCT	%	37.2		36.2	35.4	35.4		37.6	37.4	37.4	± 1.0
	l/l	0.372		0.362	0.354	0.354		0.376	0.374	0.374	± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	239		240	260	260		255	260	260	± 10
VMP MPV	µm ³ ; fl	10.0		N/A	N/A	N/A		N/A	N/A	N/A	± 0.5

Ref: TEMP-0387 Rev.52 BACK / VERSO 1300113555