

**LOT**
**CX 498**
**CAL**

**(Exp.) 2024-10-05**

(YYYY - MM - DD)

 Rev **1**

| PARAMETRES<br>PARAMETERS | UNITES<br>UNITS                                       | WHITEDIFF                  |  |              |                 |              |  |                     |                                      |              | TOLERANCES<br>TOLERANCE |
|--------------------------|-------------------------------------------------------|----------------------------|--|--------------|-----------------|--------------|--|---------------------|--------------------------------------|--------------|-------------------------|
|                          |                                                       | YUMIZEN                    |  | YUMIZEN      | YUMIZEN         | YUMIZEN      |  | YUMIZEN             | YUMIZEN                              | YUMIZEN      |                         |
|                          |                                                       | H500 OT<br>H500 CT<br>H550 |  | H500 OT      | H500 CT<br>H550 | H560         |  | H500 OT<br>H500E OT | H500 CT<br>H500E CT<br>H550<br>H550E | H560         |                         |
|                          |                                                       | v1.0 to v2.x               |  |              | v3.x Only       | v3.0 to v3.3 |  |                     | Since v4.x                           | Since v3.4   |                         |
| GB WBC                   | 10 <sup>3</sup> /mm <sup>3</sup> ;10 <sup>9</sup> /l  | <b>8.90</b>                |  | <b>8.90</b>  | <b>8.90</b>     | <b>8.90</b>  |  | <b>8.90</b>         | <b>8.90</b>                          | <b>8.90</b>  | ± 0.20                  |
| GR RBC                   | 10 <sup>6</sup> /mm <sup>3</sup> ;10 <sup>12</sup> /l | <b>4.45</b>                |  | <b>4.41</b>  | <b>4.41</b>     | <b>4.41</b>  |  | <b>4.45</b>         | <b>4.45</b>                          | <b>4.45</b>  | ± 0.06                  |
| HB HGB                   | g/dl                                                  | <b>12.6</b>                |  | <b>12.6</b>  | <b>12.6</b>     | <b>12.6</b>  |  | <b>12.8</b>         | <b>12.8</b>                          | <b>12.8</b>  | ± 0.2                   |
|                          | g/l                                                   | <b>126</b>                 |  | <b>126</b>   | <b>126</b>      | <b>126</b>   |  | <b>128</b>          | <b>128</b>                           | <b>128</b>   | ± 2                     |
|                          | mmol/l                                                | <b>7.82</b>                |  | <b>7.82</b>  | <b>7.82</b>     | <b>7.82</b>  |  | <b>7.95</b>         | <b>7.95</b>                          | <b>7.95</b>  | ± 0.12                  |
| HT HCT                   | %                                                     | <b>36.5</b>                |  | <b>35.4</b>  | <b>35.2</b>     | <b>35.2</b>  |  | <b>37.5</b>         | <b>37.5</b>                          | <b>37.5</b>  | ± 1.0                   |
|                          | l/l                                                   | <b>0.365</b>               |  | <b>0.354</b> | <b>0.352</b>    | <b>0.352</b> |  | <b>0.375</b>        | <b>0.375</b>                         | <b>0.375</b> | ± 0.010                 |
| PLA PLT                  | 10 <sup>3</sup> /mm <sup>3</sup> ;10 <sup>9</sup> /l  | <b>232</b>                 |  | <b>248</b>   | <b>255</b>      | <b>255</b>   |  | <b>242</b>          | <b>256</b>                           | <b>256</b>   | ± 10                    |
| VMP MPV                  | µm <sup>3</sup> ; fl                                  | <b>10.2</b>                |  | N/A          | N/A             | N/A          |  | N/A                 | N/A                                  | N/A          | ± 0.5                   |

Ref: TEMP-0387 Rev.52 1300113555 BACK / VERSO