

LOT
CX 500
CAL

(Exp.) 2024-12-05

(YYYY - MM - DD)

 Rev **1**

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN		YUMIZEN	YUMIZEN	YUMIZEN		YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550		H500 OT	H500 CT H550	H560		H500 OT H500E OT	H500 CT H500E CT H550 H550E	H560	
		v1.0 to v2.x			v3.x Only	v3.0 to v3.3			Since v4.x	Since v3.4	
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.50		8.50	8.50	8.50		8.50	8.50	8.50	± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.50		4.45	4.45	4.45		4.50	4.50	4.50	± 0.06
HB HGB	g/dl	12.8		12.8	12.8	12.8		12.8	12.8	12.8	± 0.2
	g/l	128		128	128	128		128	128	128	± 2
	mmol/l	7.95		7.95	7.95	7.95		7.95	7.95	7.95	± 0.12
HT HCT	%	36.9		35.9	35.7	35.7		37.7	37.6	37.6	± 1.0
	l/l	0.369		0.359	0.357	0.357		0.377	0.376	0.376	± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	236		241	252	252		243	253	253	± 10
VMP MPV	μm ³ ; fl	10.1		N/A	N/A	N/A		N/A	N/A	N/A	± 0.5

Ref: TEMP-0387 Rev.52 1300113555 BACK / VERSO