

LOT

CX 512

CAL



(Exp.) 2025-12-05

(YYYY - MM - DD)

Rev **1**

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN		YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550 v1.0 to v2.x		H500 OT v3.x Only	H500 CT H550	H560 v3.0 to v3.3	H500 OT H500E OT Since v4.x	H500 CT H500E CT H550 H550E	H500 CRP	H560 Since v3.4	
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.75		8.60	8.60	8.60	8.65	8.65	8.65	8.65	± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.38		4.33	4.33	4.33	4.34	4.34	4.34	4.34	± 0.06
HB HGB	g/dl	12.4		12.4	12.4	12.4	12.4	12.4	12.4	12.4	± 0.2
	g/l	124		124	124	124	124	124	124	124	± 2
	mmol/l	7.70		7.70	7.70	7.70	7.70	7.70	7.70	7.70	± 0.12
HT HCT	%	36.1		34.2	33.3	33.3	36.0	36.1	36.1	36.1	± 1.0
	l/l	0.361		0.342	0.333	0.333	0.360	0.361	0.361	0.361	± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	234		235	246	246	238	249	249	249	± 10
VMP MPV	μm ³ ; fl	9.3		N/A	N/A	N/A	N/A	N/A	N/A	N/A	± 0.5

Ref: TEMP-0387 Rev.53