

LOT

CX 513

CAL



(Exp.) 2026-01-05

(YYYY - MM - DD)

Rev 1

| PARAMETRES PARAMETERS | UNITES UNITS | WHITEDIFF | | | | | | | | | | TOLERANCES TOLERANCE |
|--------------------------|---|--|------------------------------|-------------------------------------|------------------------------|---------------------------------------|--|----------------------------------|------------------------------|----------------------------|----------------------------|-------------------------|
| | | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | YUMIZEN | |
| | | H500 OT H500 CT H550 v1.0 to v2.x | H500 OT v3.x Only | H500 CT H550 v3.0 to v3.3 | H560 v3.0 to v3.3 | H500 OT H500E OT Since v4.x | H500 CT H500E CT H550 H550E Since v4.x | H500 CRP v3.0 to v3.3 | H560 v3.0 to v3.3 | H560 Since v3.4 | H560 Since v3.4 | |
| GB WBC | 10 ³ /mm ³ ;10 ⁹ /l | 8.70 | | 8.50 | 8.50 | 8.50 | 8.55 | 8.55 | 8.55 | 8.55 | ± 0.20 | |
| GR RBC | 10 ⁶ /mm ³ ;10 ¹² /l | 4.38 | | 4.31 | 4.31 | 4.31 | 4.35 | 4.35 | 4.35 | 4.35 | ± 0.06 | |
| HB HGB | g/dl | 12.6 | | 12.6 | 12.6 | 12.6 | 12.6 | 12.6 | 12.6 | 12.6 | ± 0.2 | |
| | g/l | 126 | | 126 | 126 | 126 | 126 | 126 | 126 | 126 | ± 2 | |
| | mmol/l | 7.82 | | 7.82 | 7.82 | 7.82 | 7.82 | 7.82 | 7.82 | 7.82 | ± 0.12 | |
| HT HCT | % | 36.6 | | 34.3 | 33.6 | 33.6 | 35.9 | 35.1 | 35.1 | 35.1 | ± 1.0 | |
| | l/l | 0.366 | | 0.343 | 0.336 | 0.336 | 0.359 | 0.351 | 0.351 | 0.351 | ± 0.010 | |
| PLA PLT | 10 ³ /mm ³ ;10 ⁹ /l | 244 | | 242 | 252 | 252 | 244 | 255 | 255 | 255 | ± 10 | |
| VMP MPV | µm ³ ; fl | 10.4 | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | ± 0.5 | |

Ref: TEMP-0387 Rev.53