

LOT

CX 515

CAL



(Exp.) 2026-03-05

(YYYY - MM - DD)

Rev 1

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550 v1.0 to v2.x	H500 OT v3.x Only	H500 CT H550	H560 v3.0 to v3.3	H500 OT H500E OT v3.0 to v3.3	H500 CT H500E CT H550 H550E Since v4.x	H500 CRP	H560 Since v3.4		
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.65	8.60	8.60	8.60	8.55	8.55	8.55	8.55	± 0.20	
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.39	4.35	4.35	4.35	4.42	4.37	4.37	4.37	± 0.06	
HB HGB	g/dl	12.2	12.2	12.2	12.2	12.3	12.2	12.2	12.2	± 0.2	
	g/l	122	122	122	122	123	122	122	122	± 2	
	mmol/l	7.58	7.58	7.58	7.58	7.64	7.58	7.58	7.58	± 0.12	
HT HCT	%	36.0	33.7	33.1	33.1	35.8	35.1	35.1	35.1	± 1.0	
	l/l	0.360	0.337	0.331	0.331	0.358	0.351	0.351	0.351	± 0.010	
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	249	254	257	257	251	257	257	257	± 10	
VMP MPV	µm ³ ; fl	10.4	N/A	N/A	N/A	N/A	N/A	N/A	N/A	± 0.5	

Ref: TEMP-0387 Rev.53