

LOT

CX 516

CAL



(Exp.) 2026-04-05

(YYYY - MM - DD)

Rev **1**

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN		YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550		H500 OT	H500 CT H550	H560	H500 OT H500E OT	H500 CT H500E CT H550 H550E	H500 CRP	H560	
		v1.0 to v2.x			v3.x Only	v3.0 to v3.3		Since v4.x		Since v3.4	
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.65		8.60	8.60	8.60	8.50	8.65	8.65	8.65	± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.43		4.41	4.41	4.41	4.43	4.40	4.40	4.40	± 0.06
HB HGB	g/dl	12.9		12.8	12.8	12.8	12.8	12.7	12.7	12.7	± 0.2
	g/l	129		128	128	128	128	127	127	127	± 2
	mmol/l	8.01		7.95	7.95	7.95	7.95	7.89	7.89	7.89	± 0.12
HT HCT	%	37.2		35.1	34.6	34.6	36.8	36.9	36.9	36.9	± 1.0
	l/l	0.372		0.351	0.346	0.346	0.368	0.369	0.369	0.369	± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	233		232	240	240	234	233	233	233	± 10
VMP MPV	µm ³ ; fl	10.2		N/A	N/A	N/A	N/A	N/A	N/A	N/A	± 0.5

Ref: TEMP-0387 Rev.53