

LOT

CX 516

CAL



(Exp.) 2026-04-05

(YYYY - MM - DD)

Rev 1

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF									TOLERANCES TOLERANCE
		YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550 v1.0 to v2.x	H500 OT v3.x Only	H500 CT H550 v3.0 to v3.3	H560 v3.0 to v3.3	H500 OT H500E OT Since v4.x	H500 CT H500E CT H550 H550E	H500 CRP	H560 Since v3.4		
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.65		8.60	8.60	8.60	8.50	8.65	8.65	8.65	± 0.20
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.43		4.41	4.41	4.41	4.43	4.40	4.40	4.40	± 0.06
HB HGB	g/dl	12.9		12.8	12.8	12.8	12.8	12.7	12.7	12.7	± 0.2
	g/l	129		128	128	128	128	127	127	127	± 2
	mmol/l	8.01		7.95	7.95	7.95	7.95	7.89	7.89	7.89	± 0.12
HT HCT	%	37.2		35.1	34.6	34.6	36.8	36.9	36.9	36.9	± 1.0
	l/l	0.372		0.351	0.346	0.346	0.368	0.369	0.369	0.369	± 0.010
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	233		232	240	240	234	233	233	233	± 10
VMP MPV	μm ³ ; fl	10.2		N/A	N/A	N/A	N/A	N/A	N/A	N/A	± 0.5

Ref: TEMP-0387 Rev.53