

LOT

CX 517

Rev 1

CAL



(Exp.) 2026-05-05

(YYYY - MM - DD)

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF										TOLERANCES TOLERANCE
		YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550 v1.0 to v2.x	H500 OT v3.x Only	H500 CT H550	H560 v3.0 to v3.3	H500 OT H500E OT v3.0 to v3.3	H500 CT H500E CT H550 H550E Since v4.x	H500 CRP	H560 Since v3.4	H560	H560	
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.60		8.60	8.60	8.60	8.65	8.65	8.65	8.65	± 0.20	
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.48		4.46	4.46	4.46	4.54	4.51	4.51	4.51	± 0.06	
HB HGB	g/dl	12.8		12.8	12.8	12.8	12.9	12.7	12.7	12.7	± 0.2	
	g/l	128		128	128	128	129	127	127	127	± 2	
	mmol/l	7.95		7.95	7.95	7.95	8.01	7.89	7.89	7.89	± 0.12	
HT HCT	%	36.7		34.6	34.6	34.6	37.2	36.6	36.6	36.6	± 1.0	
	l/l	0.367		0.346	0.346	0.346	0.372	0.366	0.366	0.366	± 0.010	
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	232		236	248	248	240	238	238	238	± 10	
VMP MPV	µm ³ ; fl	10.1		N/A	N/A	N/A	N/A	N/A	N/A	N/A	± 0.5	

Ref: TEMP-0387 Rev.53