

LOT

CX 519

CAL



(Exp.) 2026-07-05

(YYYY - MM - DD)

Rev 1

PARAMETRES PARAMETERS	UNITES UNITS	WHITEDIFF										TOLERANCES TOLERANCE
		YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	YUMIZEN	
		H500 OT H500 CT H550 v1.0 to v2.x	H500 OT v3.x Only	H500 CT H550	H560 v3.0 to v3.3	H500 OT H500E OT v3.0 to v3.3	H500 CT H500E CT H550 H550E Since v4.x	H500 CRP	H560 Since v3.4			
GB WBC	10 ³ /mm ³ ;10 ⁹ /l	8.85	8.75	8.75	8.75	8.85	8.85	8.85	8.85	8.85	± 0.20	
GR RBC	10 ⁶ /mm ³ ;10 ¹² /l	4.34	4.30	4.30	4.30	4.36	4.36	4.36	4.36	4.36	± 0.06	
HB HGB	g/dl	12.4	12.5	12.5	12.5	12.3	12.3	12.3	12.3	12.3	± 0.2	
	g/l	124	125	125	125	123	123	123	123	123	± 2	
	mmol/l	7.70	7.76	7.76	7.76	7.64	7.64	7.64	7.64	7.64	± 0.12	
HT HCT	%	35.8	33.8	33.3	33.3	35.5	35.3	35.3	35.3	35.3	± 1.0	
	l/l	0.358	0.338	0.333	0.333	0.355	0.353	0.353	0.353	0.353	± 0.010	
PLA PLT	10 ³ /mm ³ ;10 ⁹ /l	239	240	257	257	243	246	246	246	246	± 10	
VMP MPV	µm ³ ; fl	9.9	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	± 0.5	

Ref: TEMP-0387 Rev.53